



ET10

Terminal Type - ET10 , Ground modular terminal block , connection method: Screw connection, number of connections: 2, Rated cross section: 10 mm², cross section: 1.5 mm² - 16 mm², AWG: 16 - 6 , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	ET10
Connection Method	Screw Connection
Rating	10 mm ² / 1.2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	10 mm	0.39 inch
Length	44.3 mm	1.74 inch
Height	45.7 mm	1.8 inch
Weight of std. Packing Unit	1.65 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	16 mm ²

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	1.5 mm ²

Conductor cross section solid max	16 mm ²
-----------------------------------	--------------------

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	0 V
ATEX Nominal Current I _n	A
ATEX Cross Sec. Flexible Max.	10 mm ²

Ratings - CSA


CSA Standard	CSA C22.8 NO 158
B - CSA Nominal Voltage U _N	0 V
B - CSA Nominal Current I _N	A
B - CSA Wire Min	16 AWG
B - CSA Wire Max	6 AWG

Ratings - UL


UL Standard	UL 1059
B - UL Nominal Voltage U _N	0 V
B - UL Nominal Current I _N	A
B - UL Wire Min	16 AWG
B - UL Wire Max	6 AWG

Product Accessories

Cover Profile








PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---





Cover Profile Carrier

UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	

End Clamp		
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN10	Width : 10.00 mm	
Partition Plate		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	