



ET35

Terminal Type - ET35 , Ground modular terminal block , connection method: Screw connection, number of connections: 2, Rated cross-section: 35 mm², cross-section: 6 mm² - 35 mm², AWG: 8 - 1 , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	ET35
Connection Method	Screw Connection
Rating	35 mm ² / 3 Nm
HSN Number	8904476704276
Standard Packing Qty (in No)	20
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	16.5 mm	0.65 inch
Length	58 mm	2.28 inch
Height	63 mm	2.48 inch
Weight of std. Packing Unit	2.09 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	6 mm ²
Conductor cross section solid max	35 mm ²

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	6 mm ²

Conductor cross section solid max	35 mm ²
-----------------------------------	--------------------

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	0 V
ATEX Nominal Current I _n	0 A
ATEX Cross Sec. Flexible Max.	35 mm ²

Ratings - CSA











CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	0 V
B - CSA Nominal Current I _N	0 A
B - CSA Wire Min	8 AWG
B - CSA Wire Max	1 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	0 V
B - UL Nominal Current I _N	0 A
B - UL Wire Min	8 AWG
B - UL Wire Max	1 AWG

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	

End Clamp		
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	