


FDBK1X6

Terminal Type - FDBK1X6 , Distribution Block, nominal voltage: 800 V, nominal current: IC-64 A , OG-32 A , connection method: 1 Nut connection for IC & Screw connection for OG, number of connections: 13, Rated cross-section - IC-25 mm² , OG-4 mm² , cross section: IC-10 -25 mm² , OG-0.5 - 6 mm² , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	FDBK1X6
Connection Method	1 nut connection for IC & Screw clamp connection for OG
Rating	800 V / IC-64 A, OG-32 A / IC-25 mm ² , OG-4 mm ² / IC-2.5 Nm , OG-0.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	IC-M6 , OG-M3

Dimensions & Weight

Width	61.5 mm	2.42 inch
Length	67.5 mm	2.66 inch
Height	49.9 mm	1.96 inch
Weight of std. Packing Unit	1.24 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	IC-10 mm ² , OG-0.5 mm ²
Conductor cross section flexible max	C-25 mm ² , OG-4 mm ²
Conductor cross section solid min	IC-10 mm ² , OG-0.5 mm ²
Conductor cross section solid max	IC-25 mm ² , OG-6 mm ²

Rated Conductor Size

Conductor cross section flexible min	IC-10 mm ² , OG-0.5 mm ²
Conductor cross section flexible max	C-25 mm ² , OG-4 mm ²


Conductor cross section solid min	IC-10 mm ² , OG-0.5 mm ²
Conductor cross section solid max	IC-25 mm ² , OG-6 mm ²

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	80 A
B - UL Wire Min	IC-12 , OG-20 AWG
B - UL Wire Max	IC-4, OG-10 AWG

Product Accessories

Cover Profile

PCPDBF-4	Height : 13.10 mm Thickness : 1.00 mm Length : 95.00 mm	
----------	---	---


DIN Rail Perforated








CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	


DIN Rail, Unperforated



CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
DBF-4	Height : 45.40 mm Thickness : 3.00 mm Length : 90.00 mm	
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	

Partition Plate		
KBX	Height : 43.00 mm Thickness : 1.50 mm Length : 54.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	