


KATM4

Terminal Type - KATM4 , Feed Through Terminal Block, nominal voltage: 1000 V, nominal current: 57 A, connection method: Bolt Connection - Screw driver operated , number of connections: 2, cross section: 0.5 mm² - 10 mm², AWG: 14 - 8, mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KATM4
Connection Method	Bolt Connection
Rating	1000 V / 57 A / 10 mm ² / 1.2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	INDIA
Screw thread	M4

Dimensions & Weight

Width	13 mm	0.51 inch
Length	50 mm	1.97 inch
Height	41.4 mm	1.63 inch
Weight of std. Packing Unit	0.99 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	630 V
ATEX Nominal Current I _n	57 A
ATEX Cross Sec. Flexible Max.	10 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	600 V
B - CSA Nominal Current I _N	50 A
B - CSA Wire Min	14 AWG
B - CSA Wire Max	8 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	50 A
B - UL Wire Min	14 AWG
B - UL Wire Max	8 AWG








Product Accessories








Cover Profile

PCC3K	Height : 17.50 mm Width : 50.00 mm Thickness : 1.50 mm	
PCCM26K	Height : 13.00 mm Width : 54.50 mm Thickness : 1.00 mm	
PCCM39K	Height : 3.00 mm Width : 54.50 mm Thickness : 1.00 mm	



DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
-------	--	---

DIN Rail Perforated			
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm		
DIN Rail, Unperforated			
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm		
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm		
End Cap			
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm		
End Clamp			
SCUP	Height : 34.00 mm Length : 44.75 mm		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm		

End Clamp		
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPS4	Height : 32.00 mm Width : 1.50 mm Length : 50.00 mm	
Insertion Bridge		
KSL4-2W	Width : 20.50 mm Pitch : 13.00 mm Length : 27.50 mm	
KSL4-10W	Width : 124.50 mm Pitch : 13.00 mm Length : 26.50 mm	
KSL4-3W	Width : 33.50 mm Pitch : 13.00 mm Length : 26.50 mm	
KSL4-4W	Width : 46.50 mm Pitch : 13.00 mm Length : 26.50 mm	
KSL4-5W	Width : 59.50 mm Pitch : 13.00 mm Length : 26.20 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	

Partition Plate		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	