


## KDPT35

Terminal Type - KDPT35 ,Test - Disconnect terminal block, nominal voltage: 1500 V, nominal current: 30 A, Rated Cross Section : 6 mm<sup>2</sup> connection method: Screw connection, number of connections: 2, cross section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 32



### Approvals



### General Information

|                              |                                               |
|------------------------------|-----------------------------------------------|
| Product Name                 | KDPT35                                        |
| Connection Method            | Screw Connection                              |
| Rating                       | 1500 V / 30 A / 6.00 mm <sup>2</sup> / 1.2 Nm |
| HSN Number                   | 85389000                                      |
| Standard Packing Qty (in No) | 10                                            |
| Country Of Origin            | INDIA                                         |
| Screw thread                 | M3.5                                          |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 15 mm   | 0.59 inch |
| Length                      | 138 mm  | 5.43 inch |
| Height                      | 79 mm   | 3.11 inch |
| Weight of std. Packing Unit | 0.82 Kg |           |

### Material Data

|                     |                                         |
|---------------------|-----------------------------------------|
| Insulating Material | Polyamide 6,6                           |
| Standard Colour     | Gray                                    |
| Colour Variants     | Red, Yellow, Blue, Black, Green, Khakhi |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 6 mm <sup>2</sup>   |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 10 mm <sup>2</sup>  |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 6 mm <sup>2</sup>   |


|                                   |                     |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max | 10 mm <sup>2</sup>  |

## Product Accessories


### DIN Rail Perforated

|       |                                                                                      |                                                                                     |
|-------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| CHKDS | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |  |
| CHKS  | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |


### DIN Rail, Unperforated

|      |                                                              |                                                                                      |
|------|--------------------------------------------------------------|--------------------------------------------------------------------------------------|
| CHKD | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |   |
| CHK  | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm  |  |

### End Cap

|           |                                                           |                                                                                       |
|-----------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKENDCAP | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm |  |
|-----------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|

### End Cover

|        |                                                            |                                                                                       |
|--------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| KDPTEP | Height : 65.00 mm<br>Width : 2.50 mm<br>Length : 138.00 mm |  |
|--------|------------------------------------------------------------|---------------------------------------------------------------------------------------|

### Marker For Terminal Blocks

|            |                  |                                                                                       |
|------------|------------------|---------------------------------------------------------------------------------------|
| LABEL KN10 | Width : 10.00 mm |  |
|------------|------------------|---------------------------------------------------------------------------------------|

### Isolating Plug

|        |                                                                |                                                                                       |
|--------|----------------------------------------------------------------|---------------------------------------------------------------------------------------|
| KDPTDP | Height : 46.10 mm<br>Thickness : 10.00 mm<br>Length : 43.45 mm |  |
|--------|----------------------------------------------------------------|---------------------------------------------------------------------------------------|