


KLTD4

Terminal Type - KLTD4, Test Disconnect terminal block, nominal voltage: 1000 V (Tested At - 1100 V) , nominal current: 41 A, connection method: Bolt Connection, number of connections: 2, Rated cross section: 6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KLTD4
Connection Method	Bolt Connection
Rating	1000 V / 41 A / 6 mm ² / 2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	12 mm	0.47 inch
Length	74 mm	2.91 inch
Height	49.5 mm	1.95 inch
Weight of std. Packing Unit	1.86 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Product Accessories

Cover Profile

PCCM24	Height : 21.00 mm Width : 75.50 mm Thickness : 1.00 mm	
PCCM36	Height : 21.00 mm Width : 75.50 mm Thickness : 1.25 mm	
PCD3	Height : 26.20 mm Width : 73.00 mm Thickness : 1.50 mm	


DIN Rail Perforated







CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	

DIN Rail, Unperforated


CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	




End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPLD	Height : 49.70 mm Width : 1.50 mm Length : 72.75 mm	
Insertion Bridge		
KDSL4-10W	Width : 115.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-3W	Width : 31.50 mm Pitch : 12.00 mm Length : 27.00 mm	

Insertion Bridge		
KDSL4-4W	Width : 43.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-5W	Width : 55.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-6W	Width : 67.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-2W	Width : 19.50 mm Pitch : 12.00 mm Length : 27.00 mm	

Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	