

KNL35

Neutral link Type - KNL35 , Neutral link for shield on busbars, Nominal voltage: 800 V , Nominal current: 125 A, Connection method: Screw connection, number of connections: 1, Rated cross section: 35.0 mm² , cross section: 10.0 mm² - 35.0 mm², mounting type: Neutral Busbar



Approvals



General Information

Product Name	KNL35
Connection Method	Screw Connection
Rating	800 V / 125 A / 35 mm ² / 3.0 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	14.3 mm	0.56 inch
Length	27.3 mm	1.07 inch
Height	35 mm	1.38 inch
Weight of std. Packing Unit	1.13 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green
Colour Variants	Black, Green

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	35 mm ²

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	35 mm ²


Conductor cross section solid min	10 mm ²
Conductor cross section solid max	35 mm ²

Product Accessories


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Clamp

SCNL	Height : 44.10 mm Width : 9.50 mm Length : 50.00 mm	
------	---	---

Marker For Terminal Blocks

LABEL KN12	Width : 12.00 mm	
------------	------------------	---

Support Bracket

KNLSUP	Height : 18.35 mm Width : 19.00 mm Length : 23.00 mm	
--------	--	---

Neutral busbar

KNLB10	Width : 10.00 mm Thickness : 3.00 mm Length : 1,000.00 mm	
--------	---	---

Neutral busbar				
KNLB6	Width	: 6.00 mm		
	Thickness	: 6.00 mm		
	Length	: 1,000.00 mm		

