



## KUDDF4AD48V

Terminal Type - KUDDF4AD48V, Fuse terminal block with LED of 48 V AC/ V DC for fuse failure indication, nominal voltage: 630 V, nominal current: UT-6.3 A / LT 28 A , suitable size of cartridge fuse : 5X20 mm and 5x25 mm , Rated cross-section – 2.5 mm<sup>2</sup> , connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS 35/7.5 , TS 35/15 , TS 32



### Approvals



### General Information

Product Name	KUDDF4AD48V
Connection Method	Screw Connection
Rating	630 V / UT-6.3 A , LT-28 A / 2.5 mm <sup>2</sup> / 0.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	8 mm	0.31 inch
Length	74 mm	2.91 inch
Height	62 mm	2.44 inch
Weight of std. Packing Unit	1.18 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
--------------------------------------	---------------------


Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

**Product Accessories**

<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Insertion Bridge		
UFSL-10W	Height : 79.50 mm Pitch : 8.20 mm Length : 22.50 mm	
UFSL-3W	Width : 22.10 mm Pitch : 8.20 mm Length : 22.50 mm	
UFSL-4W	Width : 30.30 mm Pitch : 8.20 mm Length : 22.50 mm	
UFSL-5W	Width : 38.50 mm Pitch : 8.20 mm Length : 22.50 mm	
UFSL-2W	Width : 13.00 mm Pitch : 8.20 mm Length : 22.50 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	

Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	

Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	