


KULTD6FT

Terminal Type - KULTD6FT , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 41 A , connection method: Screw connection with spring support , number of connections: 2, cross section: 0.5 mm² - 10 mm² , AWG: 24-8, mounting type: TS 35/7.5, TS 35/15, and TS 32



Approvals



General Information

Product Name	KULTD6FT
Connection Method	Screw Connection with spring support
Rating	1000 V / 41 A / 6 mm ² / 1 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	85.2 mm	3.35 inch
Height	71.5 mm	2.81 inch
Weight of std. Packing Unit	1.98 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²



Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Product Accessories


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	




DIN Rail, Unperforated



CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	









End Cap








CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---


End Clamp

SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPSLD	Height : 46.40 mm Width : 2.00 mm Length : 85.10 mm	
Fixed Bridge		
CCLAKG6(4+1)AW	Height : 65.65 mm Width : 9.80 mm Length : 64.45 mm	
CCLAKG6-10W	Pitch : 8.00 mm Length : 80.45 mm	
CCLAKG6-2W	Pitch : 8.00 mm Length : 16.45 mm	
CCLAKG6-3W	Pitch : 8.00 mm Length : 24.45 mm	
CCLAKG6-4W	Pitch : 8.00 mm Length : 32.45 mm	

Fixed Bridge		
CCLAKG6-5W	Pitch : 8.00 mm Length : 40.45 mm	
CCLAKG6-6W	Pitch : 8.00 mm Length : 48.45 mm	
Insertion Bridge		
KUSLD6(2)AW	Width : 24.45 mm Length : 11.25 mm	
KUSLD6(2+1)AW	Width : 34.00 mm Length : 11.25 mm	
KUSLD6(3)AW	Width : 40.45 mm Length : 11.25 mm	
KUSLD6(3+1)AW	Width : 48.45 mm Length : 11.25 mm	
KUSLD6(4)AW	Width : 56.45 mm Length : 11.25 mm	
KUSLD6(4+1)AW	Width : 56.45 mm Length : 11.25 mm	
KSLD6-10W	Width : 79.00 mm Pitch : 8.00 mm Length : 34.00 mm	
KSLD6-2W	Width : 15.00 mm Pitch : 8.00 mm Length : 34.00 mm	
KSLD6-3W	Width : 23.00 mm Pitch : 8.00 mm Length : 34.00 mm	

Insertion Bridge		
KSLD6-7W	Height : 34.00 mm Width : 3.20 mm Thickness : 1.20 mm Pitch : 8.00 mm Length : 55.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Switching Jumper		
SLD6-2W	Height : 13.60 mm Pitch : 8.00 mm Length : 14.60 mm	
SLD6-3W	Height : 13.60 mm Pitch : 8.00 mm Length : 22.60 mm	
SLD6-4W	Height : 13.60 mm Pitch : 8.00 mm Length : 30.60 mm	
SLD6-5W	Height : 13.60 mm Pitch : 8.00 mm Length : 38.60 mm	
SLD6-6W	Height : 13.60 mm Pitch : 8.00 mm Length : 46.40 mm	
SLD6-10W	Height : 13.60 mm Pitch : 8.00 mm Length : 78.60 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

Marker carriers		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	

