


KULTD6FT

Terminal Type - KULDT6FT , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 41 A , connection method: Screw connection with spring support , number of connections: 2, cross section: 0.5 mm² - 10 mm² , AWG: 24-8, mounting type: TS 35/7.5, TS 35/15, and TS 32



Approvals



General Information

| | |
|------------------------------|--|
| Product Name | KULTD6FT |
| Connection Method | Screw Connection with spring support |
| Rating | 1000 V / 41 A / 6 mm ² / 1 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty (in No) | 50 |
| Country Of Origin | India |
| Screw thread | M3.5 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 8 mm | 0.31 inch |
| Length | 85.2 mm | 3.35 inch |
| Height | 71.5 mm | 2.81 inch |
| Weight of std. Packing Unit | 1.98 Kg | |

Material Data

| | |
|---------------------|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red, Yellow, Blue, Black, Green, Khakhi |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 6 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 10 mm ² |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 6 mm ² |











| | |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 10 mm ² |



Product Accessories

| DIN Rail Perforated | | |
|-------------------------------|--|---|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
| End Clamp | | |
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |

| End Clamp | | |
|----------------|--|---|
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm |  |
| DCKN10 | Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| End Cover | | |
| KPSLD | Height : 46.40 mm Width : 2.00 mm Length : 85.10 mm |  |
| Fixed Bridge | | |
| CCLAKG6(4+1)AW | Height : 65.65 mm Width : 9.80 mm Length : 64.45 mm |  |
| CCLAKG6-10W | Pitch : 8.00 mm Length : 80.45 mm |  |
| CCLAKG6-2W | Pitch : 8.00 mm Length : 16.45 mm |  |
| CCLAKG6-3W | Pitch : 8.00 mm Length : 24.45 mm |  |
| CCLAKG6-4W | Pitch : 8.00 mm Length : 32.45 mm |  |

| Fixed Bridge | | |
|------------------|--|---|
| CCLAKG6-5W | Pitch : 8.00 mm Length : 40.45 mm |  |
| CCLAKG6-6W | Pitch : 8.00 mm Length : 48.45 mm |  |
| Insertion Bridge | | |
| KUSLD6(2)AW | Width : 24.45 mm Length : 11.25 mm |  |
| KUSLD6(2+1)AW | Width : 34.00 mm Length : 11.25 mm |  |
| KUSLD6(3)AW | Width : 40.45 mm Length : 11.25 mm |  |
| KUSLD6(3+1)AW | Width : 48.45 mm Length : 11.25 mm |  |
| KUSLD6(4)AW | Width : 56.45 mm Length : 11.25 mm |  |
| KUSLD6(4+1)AW | Width : 56.45 mm Length : 11.25 mm |  |
| KSLD6-10W | Width : 79.00 mm Pitch : 8.00 mm Length : 34.00 mm |  |
| KSLD6-2W | Width : 15.00 mm Pitch : 8.00 mm Length : 34.00 mm |  |
| KSLD6-3W | Width : 23.00 mm Pitch : 8.00 mm Length : 34.00 mm |  |

| Insertion Bridge | | |
|----------------------------|---|---|
| KSLD6-7W | Height : 34.00 mm Width : 3.20 mm Thickness : 1.20 mm Pitch : 8.00 mm Length : 55.00 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN8 | Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm |  |
| Switching Jumper | | |
| SLD6-2W | Height : 13.60 mm Pitch : 8.00 mm Length : 14.60 mm |  |
| SLD6-3W | Height : 13.60 mm Pitch : 8.00 mm Length : 22.60 mm |  |
| SLD6-4W | Height : 13.60 mm Pitch : 8.00 mm Length : 30.60 mm |  |
| SLD6-5W | Height : 13.60 mm Pitch : 8.00 mm Length : 38.60 mm |  |
| SLD6-6W | Height : 13.60 mm Pitch : 8.00 mm Length : 46.40 mm |  |
| SLD6-10W | Height : 13.60 mm Pitch : 8.00 mm Length : 78.60 mm |  |
| Marker carriers | | |
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |

| Marker carriers | | |
|-----------------|--|---|
| DCKNMLH | Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKNMLH | Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm |  |

