


KUT4

Terminal Type - KUT4 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 32 A, Tested at - 1100 V, connection method: Screw connection, number of connections: 2, Rated cross section: 4.0 mm² , cross section: 0.5 mm² - 6 mm², AWG: 20 - 10, mounting type: TS35/7.5 , TS35/15 , TS32 and TS15



Approvals



General Information

Product Name	KUT4
Connection Method	Screw Connection
Rating	800 V / 32 A / 4 mm ² / 0.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6.7 mm	0.26 inch
Length	42.5 mm	1.67 inch
Height	46.4 mm	1.83 inch
Weight of std. Packing Unit	1.19 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	500 V

ATEX Nominal Current I_n	32 A
ATEX Cross Sec. Flexible Max.	4 mm ²

Ratings - CSA



CSA Standard	CSA 22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	35 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	10 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	35 A
B - UL Wire Min	20 AWG
B - UL Wire Max	10 AWG

Product Accessories

Cover Profile








PCPDBF-4	Height : 13.10 mm Thickness : 1.00 mm Length : 95.00 mm	
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	



Cover Profile Carrier

UHDD	Height : 74.50 mm Width : 2.00 mm Length : 55.82 mm	
------	---	---

DIN Rail Perforated

CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	

DIN Rail Perforated			
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm		
DIN Rail, Unperforated			
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm		
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm		
End Cap			
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm		
End Clamp			
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm		
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm		





End Clamp		
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPX	Height : 36.00 mm Width : 1.50 mm Length : 40.00 mm	
Fixed Bridge		
CCLA2.5-10W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 66.00 mm	
CCLA2.5-3W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 18.85 mm	
CCLA2.5-4W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 25.60 mm	
CCLA2.5-5W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 32.35 mm	
CCLA2.5-6W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 39.00 mm	
CCLA2.5-8W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 52.60 mm	
CCLA2.5-2W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 12.10 mm	

Insertion Bridge		
SLC2.5-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 12.50 mm	
SLC2.5-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 66.10 mm	
SLC2.5-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 25.90 mm	
SLC2.5-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 32.60 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Height : 2.42 mm Width : 6.70 mm Length : 8.50 mm	
Partition Plate		
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
KBX	Height : 43.00 mm Width : 1.50 mm Length : 54.00 mm	
Spacer Plate		
SBN1	Height : 12.10 mm Width : 1.37 mm Length : 15.50 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL2.5	Thickness : 1.20 mm Pitch : 6.60 mm Length : 12.60 mm	

Warning Label

WL4	Height : 25.20 mm Thickness : 1.10 mm Length : 28.80 mm	
-----	---	---

Marker carriers

SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	