


KUTSD6

Terminal Type - KUTSD6 , Disconnecting terminal block, nominal voltage: 800 V, nominal current: 41 A, Rated cross-section- 6 mm² , connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 10 mm², AWG: 20-8 , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KUTSD6
Connection Method	Screw Connection
Rating	800 V / 41 A / 6 mm ² / 1.4 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	65 mm	2.56 inch
Height	46.75 mm	1.84 inch
Weight of std. Packing Unit	1.45 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Orange, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	400 V
ATEX Nominal Current I _n	35 A
ATEX Cross Sec. Flexible Max.	6 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	600 V
B - CSA Nominal Current I _N	35 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	8 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	35 A
B - UL Wire Min	20 AWG
B - UL Wire Max	8 AWG








Product Accessories









Cover Profile


PCPDBF-3	Height : 14.10 mm Thickness : 1.50 mm Length : 79.00 mm	
----------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	

DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
KPSD	Height : 37.40 mm Thickness : 1.50 mm Length : 65.00 mm	
Insertion Bridge		
SLC6-3W	Width : 22.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-4W	Width : 30.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-5W	Width : 38.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-6W	Width : 46.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-10W	Width : 75.60 mm Pitch : 8.00 mm Length : 26.00 mm	
SLC6-2W	Width : 14.60 mm Pitch : 8.00 mm Length : 26.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Partition Plate		
DBF-3	Height : 38.40 mm Width : 3.00 mm Length : 78.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	

Marker carriers			
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm		
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm		

