



## LPT225NV

Terminal Type - LPT225NV, Feed-through terminal block, nominal voltage: 630 V, nominal current: 101 A, connection method: Screw connection, Operated by - 3 mm Allen key, number of connections: 3, cross section: IC - 16 - 25 mm<sup>2</sup>, OG - 6 - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	LPT225NV
Connection Method	Screw Connection
Rating	630 V / 101 A / IC - 25 mm <sup>2</sup> , OG - 10 mm <sup>2</sup> / 2.5 Nm
HSN Number	NAV
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	M6

### Dimensions & Weight

Width	11.7 mm	0.46 inch
Length	48.9 mm	1.93 inch
Height	42.7 mm	1.68 inch
Weight of std. Packing Unit	0.48 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

### Rated Conductor Size

Conductor cross section flexible min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section flexible max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>
Conductor cross section solid min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section solid max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>


### Rated Conductor Size

Conductor cross section flexible min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section flexible max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>

Conductor cross section solid min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section solid max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>


**Product Accessories**

**Cover Profile Carrier**


UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	---


**DIN Rail Perforated**

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
-------	--	---

CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
------	---	---

**DIN Rail, Unperforated**

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
------	--	---

CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
-----	---	---

**End Cap**

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

**Marker For Terminal Blocks**

LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
------------	--	---