



## LPT325NV

Terminal Type - LPT325NV , Feed-through terminal block, nominal voltage: 630 V, nominal current: 101 A, connection method: Screw connection, Operated by - 3 mm Allen key , number of connections: 4 , cross section: IC - 16 - 25 mm<sup>2</sup>, OG - 6 - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	LPT325NV
Connection Method	Screw Connection
Rating	630 V / 101 A / IC - 25 mm <sup>2</sup> , OG - 10 mm <sup>2</sup> / 2.5 Nm
HSN Number	NAV
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	M6

### Dimensions & Weight

Width	11.7 mm	0.46 inch
Length	56.3 mm	2.22 inch
Height	58 mm	2.28 inch
Weight of std. Packing Unit	0.48 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

### Rated Conductor Size






Conductor cross section flexible min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section flexible max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>
Conductor cross section solid min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section solid max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section flexible max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>

Conductor cross section solid min	IC-16 mm <sup>2</sup> , OG-6 mm <sup>2</sup>
Conductor cross section solid max	IC-25 mm <sup>2</sup> , OG-10 mm <sup>2</sup>

**Product Accessories**

<b>Cover Profile Carrier</b>		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	