


MCT2.5

Terminal Type -MCT2.5 , Mini and Micro Terminal block, nominal voltage: 500 V, nominal current: 24 A , Rated cross-section - 2.5 mm², connection method: Spring Cage Connection, number of connections: 2, cross section: 0.5 mm² - 2.5 mm², AWG : 22-14 , mounting type: Panel Mounted



Approvals



General Information

Product Name	MCT2.5
Connection Method	Spring Cage Connection
Rating	500 V / 24 A / 2.5 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	500
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	6 mm	0.24 inch
Length	30 mm	1.18 inch
Height	18 mm	0.71 inch
Weight of std. Packing Unit	1.54 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _N	400 V
ATEX Nominal Current I _N	20 A
ATEX Cross Sec. Flexible Max.	2.5 mm ²

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	300 V
B - UL Nominal Current I _N	15 A
B - UL Wire Min	22 AWG
B - UL Wire Max	14 AWG

Product Accessories


End Cover

MEP2.5	Height : 18.00 mm Width : 12.20 mm Length : 28.00 mm	
--------	--	---

Insertion Bridge

MSL2.5	Width : 10.30 mm Pitch : 5.95 mm Length : 15.14 mm	
--------	--	---

Marker For Terminal Blocks

LABEL KN5.5	Width : 6.00 mm	
-------------	-----------------	---