


MCT4

Terminal Type -MCT4, Mini and Micro Terminal Feed Through terminal block, nominal voltage: 500 V, nominal current: 32 A , Rated cross-section - 4.0 mm², connection method: Spring clamp connection, number of connections: 2, cross-section: 0.5 mm² - 4 mm², mounting type: Panel Mounted



Approvals



General Information

Product Name	MCT4
Connection Method	Spring Cage Connection
Rating	500 V / 32 A / 4 mm ²
HSN Number	8904476703989
Standard Packing Qty (in No)	200
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	7 mm	0.28 inch
Length	33.4 mm	1.31 inch
Height	23 mm	0.91 inch
Weight of std. Packing Unit	1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _N	400 V
ATEX Nominal Current I _N	24 A
ATEX Cross Sec. Flexible Max.	4 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	300 V
B - CSA Nominal Current I _N	20 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	
B - UL Nominal Voltage U _N	0 V
B - UL Nominal Current I _N	0 A
B - UL Wire Min	AWG
B - UL Wire Max	AWG

Product Accessories


End Cover

MEP4	Height : 23.00 mm Width : 13.80 mm Length : 33.40 mm	
------	--	---

Insertion Bridge

MSL4	Height : 13.90 mm Width : 10.50 mm Pitch : 7.00 mm Length : 11.75 mm	
------	---	---

Marker For Terminal Blocks

LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	
-------------	---	---