


MCT4P4

Terminal Type -MCT4P4, Feed Through terminal block, nominal voltage: 500 V, nominal current: 32 A, Rated cross-section – 4.0 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: 0.5 mm² – 4 mm², mounting type: Panel Mounted



Approvals



General Information

Product Name	MCT4P4
Connection Method	Spring Cage Connection
Rating	500 V / 32 A / 4 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	12 mm	0.47 inch
Length	33.4 mm	1.31 inch
Height	23 mm	0.91 inch
Weight of std. Packing Unit	0.78 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - CSA

CSA Standard	CSA C 22.2 NO 158
B - CSA Nominal Voltage U _N	300 V
B - CSA Nominal Current I _N	20 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	
B - UL Nominal Voltage U _N	0 V
B - UL Nominal Current I _N	0 A
B - UL Wire Min	AWG
B - UL Wire Max	AWG

Product Accessories

End Cover

MEP4	Height : 23.00 mm Width : 13.80 mm Length : 33.40 mm	
------	--	---

Insertion Bridge

MSL4	Width : 11.75 mm Length : 13.90 mm	
------	---------------------------------------	---

Marker For Terminal Blocks

LABEL KN12	Width : 12.00 mm	
------------	------------------	---