


## MCT4P4

Terminal Type -MCT4P4, Feed Through terminal block, nominal voltage: 500 V, nominal current: 32 A, Rated cross-section – 4.0 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 4, cross-section: 0.5 mm<sup>2</sup> – 4 mm<sup>2</sup>, mounting type: Panel Mounted



### Approvals



### General Information

Product Name	MCT4P4
Connection Method	Spring Cage Connection
Rating	500 V / 32 A / 4 mm <sup>2</sup>
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

### Dimensions & Weight

Width	12 mm	0.47 inch
Length	33.4 mm	1.31 inch
Height	23 mm	0.91 inch
Weight of std. Packing Unit	0.78 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>

Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C 22.2 NO 158
B - CSA Nominal Voltage U <sub>N</sub>	300 V
B - CSA Nominal Current I <sub>N</sub>	20 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	12 AWG

### Ratings - UL

UL Standard	
B - UL Nominal Voltage U <sub>N</sub>	0 V
B - UL Nominal Current I <sub>N</sub>	0 A
B - UL Wire Min	AWG
B - UL Wire Max	AWG

### Product Accessories

End Cover		
MEP4	Height : 23.00 mm Width : 13.80 mm Length : 33.40 mm	
Insertion Bridge		
MSL4	Height : 13.90 mm Width : 10.50 mm Pitch : 7.00 mm Length : 11.75 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	