


OAT2.5

Terminal Type - OAT2.5 , Feed through terminal block with secured hinged cover, nominal voltage: 1000 V, nominal current: 41 A, Rated cross-section - 6 mm², connection method: Bolt connection, number of connections: 2, cross-section: 1.5 mm² - 6 mm², AWG: 20 - 14, mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	OAT2.5
Connection Method	Bolt Connection
Rating	1000 V / 41 A / 6 mm ² / 1.2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	INDIA
Screw thread	M3

Dimensions & Weight

Width	9 mm	0.35 inch
Length	44.2 mm	1.74 inch
Height	45.2 mm	1.78 inch
Weight of std. Packing Unit	0.74 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	6 mm ²

Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	800 V
ATEX Nominal Current I _n	20 A
ATEX Cross Sec. Flexible Max.	2.5 mm ²

Ratings - CSA


CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	600 V
B - CSA Nominal Current I _N	15 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	14 AWG



Ratings - UL











UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	15 A
B - UL Wire Min	20 AWG
B - UL Wire Max	14 AWG

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	

Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	

End Clamp		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
OEP 2.5	Height : 33.50 mm Width : 1.50 mm Length : 43.50 mm	
Insertion Bridge		
OSL2.5-2W	Width : 15.00 mm Pitch : 9.00 mm Length : 25.50 mm	
OSL2.5-10W	Width : 87.00 mm Pitch : 9.00 mm Length : 25.50 mm	
OSL2.5-4W	Width : 33.00 mm Pitch : 9.00 mm Length : 25.50 mm	
OSL2.5-5W	Width : 48.00 mm Pitch : 9.00 mm Length : 25.50 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	

Marker carriers

SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	
---------	--	---

