


OAT25

Terminal Type - OAT25 , Feed through terminal block with secured hinged cover, nominal voltage: 1000 V, nominal current: 125 A, connection method: Stud type connection, number of connections: 2, cross section: 1.5 mm² - 35 mm², Rated Cross-section : 35 mm² , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	OAT25
Connection Method	Bolt Connection
Rating	1000 V / 125 A / 35 mm ² / 2.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	18 mm	0.71 inch
Length	60 mm	2.36 inch
Height	63 mm	2.48 inch
Weight of std. Packing Unit	2.41 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	35 mm ²


Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	35 mm ²

Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	35 mm ²

Product Accessories


Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

Cover Profile Carrier

UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	---


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	


DIN Rail, Unperforated








CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp




SCUP	Height : 34.00 mm Length : 44.75 mm	
------	--	---

End Clamp		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
OEP 25	Height : 53.10 mm Width : 1.50 mm Length : 60.00 mm	
Insertion Bridge		
KSL7-2W	Width : 25.50 mm Pitch : 18.00 mm Length : 31.01 mm	
KSL7-4W	Width : 61.50 mm Pitch : 18.00 mm Length : 31.03 mm	

Marker For Terminal Blocks

LABEL KN17	Width : 17.00 mm	
------------	------------------	---

Marker carriers

SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	