


## ONTM5-16C

Terminal Type - ONTM5-16C , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 76 A, connection method : Bolt Connection - Screw and Nut driver operated, number of connections: 2 , Rated Cross-section : 16 mm<sup>2</sup> , cross section: 1.5 mm<sup>2</sup> - 16 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15 , TS 32



### Approvals



### General Information

Product Name	ONTM5-16C
Connection Method	Bolt Connection
Rating	1000 V / 76 A / 16 mm <sup>2</sup> / 2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M5

### Dimensions & Weight

Width	13 mm	0.51 inch
Length	48 mm	1.89 inch
Height	36.5 mm	1.44 inch
Weight of std. Packing Unit	1.35 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	1.5 mm <sup>2</sup>
Conductor cross section flexible max	16 mm <sup>2</sup>
Conductor cross section solid min	1.5 mm <sup>2</sup>
Conductor cross section solid max	16 mm <sup>2</sup>












### Rated Conductor Size






Conductor cross section flexible min	1.5 mm <sup>2</sup>
Conductor cross section flexible max	16 mm <sup>2</sup>

Conductor cross section solid min	1.5 mm <sup>2</sup>
Conductor cross section solid max	16 mm <sup>2</sup>

**Product Accessories**

<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
ONTEP	Height : 22.80 mm Width : 2.00 mm Length : 47.80 mm	
Fixed Bridge		
CCLAONT13-2W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 17.80 mm	
CCLAONT13-10W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 121.80 mm	
CCLAONT13-3W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 30.80 mm	
CCLAONT13-4W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 43.80 mm	
CCLAONT13-5W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 56.80 mm	

Marker For Terminal Blocks		
ONTML13	Height : 2.42 mm Width : 13.00 mm Length : 11.50 mm	
Partition Plate		
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Marker carriers		
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	