


## **PAT250**

Terminal Type - PAT250, High current connectors, nominal voltage: 400 V, nominal current: 250 A, Rated cross-section - 95 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross-section: 35 mm<sup>2</sup> - 95 mm<sup>2</sup>, mounting type: Panel mounted / Surface mounted



### Approvals



### General Information

Product Name	PAT250
Connection Method	Bolt Connection
Rating	400 V / 250 A / 95 mm <sup>2</sup> / 10 Nm
HSN Number	85389000
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	M10

### Dimensions & Weight

Width	41 mm	1.61 inch
Length	102 mm	4.02 inch
Height	45.5 mm	1.79 inch
Weight of std. Packing Unit	2.3 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	35 mm <sup>2</sup>
Conductor cross section flexible max	95 mm <sup>2</sup>
Conductor cross section solid min	35 mm <sup>2</sup>
Conductor cross section solid max	95 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	35 mm <sup>2</sup>
Conductor cross section flexible max	95 mm <sup>2</sup>

Conductor cross section solid min	35 mm <sup>2</sup>
Conductor cross section solid max	95 mm <sup>2</sup>

**Product Accessories**

<b>Cover Profile</b>		
PCPAT-30-250	Height : 11.50 mm Thickness : 1.50 mm Length : 126.00 mm	
<b>End Cover</b>		
EPA100	Height : 40.00 mm Width : 27.00 mm Thickness : 5.00 mm Length : 50.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	
<b>Partition Plate</b>		
BPAT-30-250	Height : 78.50 mm Thickness : 3.00 mm Length : 120.00 mm	