


## PBTM3

Terminal Type - PBTM3 , Mini Feed-through terminal block, nominal voltage: 250 V, nominal current: 20 A, Rated cross-section - 1.5 mm<sup>2</sup>, connection method: Screw clamp connection, number of connections: 2, cross section: 0.2 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting type: Panel mounted



### Approvals



### General Information

Product Name	PBTM3
Connection Method	Screw Connection
Rating	250 V / 20 A / 1.5 mm <sup>2</sup> / 0.5 Nm
HSN Number	NAV
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	15 mm	0.59 inch
Length	25 mm	0.98 inch
Height	25 mm	0.98 inch
Weight of std. Packing Unit	0.72 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	1.5 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	1.5 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	1.5 mm <sup>2</sup>

Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	1.5 mm <sup>2</sup>

**Ratings - ATEX**

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U <sub>n</sub>	320 V
ATEX Nominal Current I <sub>n</sub>	18 A
ATEX Cross Sec. Flexible Max.	1.5 mm <sup>2</sup>

**Ratings - UL**

UL Standard	
B - UL Nominal Voltage U <sub>N</sub>	V
B - UL Nominal Current I <sub>N</sub>	A
B - UL Wire Min	AWG
B - UL Wire Max	AWG

**Product Accessories**

End Cover	
EPBM4	Height : 25.00 mm Width : 12.50 mm Length : 24.20 mm
	
Partition Plate	
MBX	Height : 36.70 mm Width : 1.50 mm Length : 43.50 mm
	