



PGQ1.5

Terminal Type - PGQ 1.5, Ground modular terminal block , connection method: push in connection , number of connections: 2, cross section: 0.08 mm² - 2.5 mm² , mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

Product Name	PGQ1.5
Connection Method	Push In Connection
Rating	1.5 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	INDIA
Screw thread	-

Dimensions & Weight

Width	3.5 mm	0.14 inch
Length	47.56 mm	1.87 inch
Height	30.7 mm	1.21 inch
Weight of std. Packing Unit	0.4 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	1.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	2.5 mm ²

Rated Conductor Size




Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	1.5 mm ²
Conductor cross section solid min	0.08 mm ²

Conductor cross section solid max	2.5 mm ²
-----------------------------------	---------------------

Product Accessories

Cover Profile		
PCPDBF-1	Height : 13.90 mm Thickness : 1.50 mm Length : 66.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSEP1.5	Height : 18.50 mm Width : 2.00 mm Length : 47.20 mm	
Marker For Terminal Blocks		
LABEL KN3.5	Height : 2.42 mm Width : 3.50 mm Length : 10.50 mm	
Partition Plate		
DBF-1	Height : 42.00 mm Width : 3.00 mm Length : 60.00 mm	
Plug-in Bridge/Jumper		
SLPU3.5-10W	Height : 21.47 mm Width : 3.00 mm Pitch : 3.50 mm Length : 34.50 mm	
SLPU3.5-2W	Height : 21.47 mm Width : 3.00 mm Pitch : 3.50 mm Length : 6.70 mm	

Plug-in Bridge/Jumper		
SLPU3.5-3W	Height : 21.47 mm Width : 3.00 mm Pitch : 3.50 mm Length : 10.20 mm	
SLPU3.5-4W	Height : 21.47 mm Width : 3.00 mm Pitch : 3.50 mm Length : 13.70 mm	
SLPU3.5-5W	Height : 21.47 mm Width : 3.00 mm Pitch : 3.50 mm Length : 17.20 mm	
SLPU3.5-6W	Height : 21.47 mm Width : 3.00 mm Pitch : 3.50 mm Length : 20.70 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	