



## PQ2.5-2T2P

Terminal Type - PQ2.5-2T2P , Multi tier Feed Through terminal block, connection method: Push-in connection/ plug connection, nominal voltage: 500 V , nominal current: 22 A , Rated cross-section - 2.5 mm<sup>2</sup> , number of connections: 4, cross-section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG : 24-12 , mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	PQ2.5-2T2P
Connection Method	Push In Connection
Rating	500 V / 22 A / 2.5 mm <sup>2</sup>
HSN Number	NAV
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	73.2 mm	2.88 inch
Height	50 mm	1.97 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>



Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

**Product Accessories**

**DIN Rail Perforated**

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

**DIN Rail, Unperforated**





CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

**End Cap**

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---





**End Clamp**




SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	




End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	



End Cover		
CSP2.5-2T2P	Height : 36.70 mm Width : 73.20 mm Thickness : 1.20 mm	

Marker For Terminal Blocks		
LABEL KN5	Height : 2.42 mm Width : 5.00 mm Length : 7.50 mm	

Plug-in Bridge/Jumper		
SLPU5-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 9.15 mm	
SLPU5-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 14.15 mm	
SLPU5-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 49.15 mm	
SLPU5-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 19.15 mm	

Plug-in Bridge/Jumper		
SLPU5-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 24.15 mm	
SLPU5-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 29.15 mm	
SLPU5-7W	Height : 26.00 mm Width : 3.00 mm Pitch : 5.00 mm Length : 34.15 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
DSDDM2.5MLH	Height : 24.10 mm Width : 5.00 mm Length : 19.70 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

PLUG		
PQPP2.5-F-10W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 50.00 mm	
PQPP2.5-F-12W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 60.00 mm	
PQPP2.5-F-14W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 70.00 mm	

<b>PLUG</b>		
PQPP2.5-F-15W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 75.00 mm	
PQPP2.5-F-2W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 10.00 mm	
PQPP2.5-F-3W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 15.00 mm	
PQPP2.5-F-4W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 20.00 mm	
PQPP2.5-F-5W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 25.00 mm	
PQPP2.5-F-6W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 30.00 mm	
PQPP2.5-F-8W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 40.00 mm	
<b>Operating lever</b>		
PQPP2.5F-LVR-1W-ORG	Height : 29.70 mm Thickness : 9.00 mm	
PQPP2.5F-LVR-2W-ORG	Height : 29.70 mm Thickness : 9.80 mm	