


PQ6-1X2

Terminal type - PQ6-1X2, Multi conductor feed-through terminal block, nominal voltage: 1000 V, nominal current: 41 A, Rated cross-section - 6 mm², connection method: Push in type, number of connections: 3, cross section: 0.2 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

Product Name	PQ6-1X2
Connection Method	Push In Connection
Rating	1000 V / 41 A / 6 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	INDIA
Screw thread	-

Dimensions & Weight

Width	8 mm	0.31 inch
Length	81.4 mm	3.2 inch
Height	42.9 mm	1.69 inch
Weight of std. Packing Unit	1.1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	6 mm ²

Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	10 mm ²

Ratings - ATEX






ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	630 V
ATEX Nominal Current I _n	36 A
ATEX Cross Sec. Flexible Max.	6 mm ²

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	40 A
B - UL Wire Min	24 AWG
B - UL Wire Max	8 AWG

Product Accessories

Cover Profile		
PCPDBF-5	Height : 14.10 mm Thickness : 1.50 mm Length : 113.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CP6-1X2	Height : 29.60 mm Width : 2.00 mm Length : 81.40 mm	

Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	
Partition Plate		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
Plug-in Bridge/Jumper		
SLPU8-2W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 15.20 mm	
SLPU8-10W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 79.20 mm	
SLPU8-3W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm	
SLPU8-4W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 31.20 mm	
SLPU8-5W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 39.20 mm	
SLPU8-6W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 47.20 mm	
SLPU8-3AW	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm	
SLPU8-7AW	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 55.20 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

