



PQF4

Terminal Type - PQF4, Fuse Terminal block, nominal voltage: 1000 V, nominal current: 6.3 A, Rated cross-section - 4 mm² - suitable size of cartridge fuse: 5X20 mm, connection method: Push-in connection, number of connections: 2, cross-section: 0.08 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

| | |
|------------------------------|------------------------------------|
| Product Name | PQF4 |
| Connection Method | Push In Connection |
| Rating | 1000 V / 6.3 A / 4 mm ² |
| HSN Number | 8904476700780 |
| Standard Packing Qty (in No) | 100 |
| Country Of Origin | India |
| Screw thread | - |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 6 mm | 0.24 inch |
| Length | 56.2 mm | 2.21 inch |
| Height | 61.1 mm | 2.41 inch |
| Weight of std. Packing Unit | 1.41 Kg | |

Material Data

| | |
|---------------------|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red, Yellow, Blue, Black, Green, Khakhi |

Rated Conductor Size

| | |
|--------------------------------------|----------------------|
| Conductor cross section flexible min | 0.08 mm ² |
| Conductor cross section flexible max | 4 mm ² |
| Conductor cross section solid min | 0.08 mm ² |
| Conductor cross section solid max | 6 mm ² |

Rated Conductor Size

| | |
|--------------------------------------|----------------------|
| Conductor cross section flexible min | 0.08 mm ² |
| Conductor cross section flexible max | 4 mm ² |

| | |
|-----------------------------------|----------------------|
| Conductor cross section solid min | 0.08 mm ² |
| Conductor cross section solid max | 6 mm ² |

Ratings - UL

| | |
|---------------------------------------|---------|
| UL Standard | UL 1059 |
| B - UL Nominal Voltage U _N | 600 V |
| B - UL Nominal Current I _N | 6.3 A |
| B - UL Wire Min | 24 AWG |
| B - UL Wire Max | 10 AWG |

Product Accessories



Cover Profile

| | | |
|----------|---|---|
| PCPDBF-6 | Height : 14.10 mm Thickness : 1.50 mm Length : 85.50 mm |  |
|----------|---|---|

DIN Rail Perforated

| | | |
|-------|--|---|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |

DIN Rail, Unperforated

| | | |
|------|--|---|
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |

End Cap

| | | |
|-----------|---|---|
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
|-----------|---|---|

End Clamp

| | | |
|------|---|---|
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
|------|---|---|

| End Clamp | | |
|-----------------------------------|--|---|
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm |  |
| DCKN10 | Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| End Cover | | |
| CPFK4 | Height : 22.70 mm Width : 2.00 mm Length : 56.20 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN5.5 | Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm |  |
| Partition Plate | | |
| DBF-6 | Height : 81.50 mm Width : 3.00 mm Length : 85.00 mm |  |

| Plug-in Bridge/Jumper | | |
|------------------------------|--|---|
| SLPU6-10W | Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 58.15 mm |  |
| SLPU6-2W | Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 10.15 mm |  |
| SLPU6-3W | Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 16.15 mm |  |
| SLPU6-4W | Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 22.15 mm |  |
| SLPU6-5W | Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 28.15 mm |  |
| SLPU6-6W | Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 34.15 mm |  |

| Marker carriers | | |
|------------------------|--|---|
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
| DCKNMLH | Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKNMLH | Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm |  |