

PQPP2.5F-15W

Plug Type - PQPP2.5F-15W , nominal voltage: 500V, nominal current: 24 A, connection method: Push-in connection, number of connections: 15, number of positions: 15, cross section: 0.08 mm² - 4 mm², AWG : 24-12



Approvals



General Information

Product Name	PQPP2.5F-15W
Connection Method	Push In Connection
Rating	500 V / 24 A / 2.5 mm ²
HSN Number	NAV
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	75 mm	2.95 inch
Length	15.8 mm	0.62 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	5.15 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²



Conductor cross section solid max	4 mm ²
-----------------------------------	-------------------

Product Accessories


Marker For Terminal Blocks

LABEL KN5.08	Pitch : 5.08 mm	
--------------	-----------------	---

Operating lever

PQPP2.5F-LVR-1W-ORG	Height : 29.70 mm Thickness : 9.00 mm	
PQPP2.5F-LVR-2W-ORG	Height : 29.70 mm Thickness : 9.80 mm	

SOCKET

PQPP2.5M-HM15W-GREY	Height : 38.00 mm Width : 18.80 mm Pitch : 5.00 mm Length : 90.50 mm	
PQPP2.5M-PFT15W-GREY	Height : 38.00 mm Width : 18.80 mm Pitch : 5.00 mm Length : 87.25 mm	
PQPP2.5M-VM15W-GREY	Height : 38.00 mm Width : 18.80 mm Pitch : 5.00 mm Length : 90.50 mm	