

## **PQPP2.5F-4W**

Plug Type - PQPP2.5F-4W , nominal voltage: 500V, nominal current: 24 A, connection method: Push-in connection, number of connections: 3, number of positions: 3, cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG : 24-12



### Approvals



### General Information

Product Name	PQPP2.5F-4W
Connection Method	Push In Connection
Rating	500 V / 24 A / 2.5 mm <sup>2</sup>
HSN Number	NAV
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

### Dimensions & Weight

Width	40 mm	1.57 inch
Length	15.8 mm	0.62 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	2.83 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>


Conductor cross section solid max	4 mm <sup>2</sup>
-----------------------------------	-------------------

**Product Accessories**

**Marker For Terminal Blocks**

LABEL KN5.08	Pitch : 5.08 mm	
--------------	-----------------	---

**Operating lever**

PQPP2.5F-LVR-1W-ORG	Height : 29.70 mm Thickness : 9.00 mm	
PQPP2.5F-LVR-2W-ORG	Height : 29.70 mm Thickness : 9.80 mm	