



## PQPP2.5M-HM8W

Socket Type - PQPP2.5M-HM8W , nominal voltage: 500V, nominal current: 24 A, connection method: Push-in connection, number of connections: 8, number of positions: 8, cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG : 24-12, mounting type: Panel mounting / Surface mounting (Horizontal type)



### Approvals



### General Information

|                              |                                    |
|------------------------------|------------------------------------|
| Product Name                 | PQPP2.5M-HM8W                      |
| Connection Method            | Push In Connection                 |
| Rating                       | 500 V / 24 A / 2.5 mm <sup>2</sup> |
| HSN Number                   | 85389000                           |
| Standard Packing Qty (in No) | 100                                |
| Country Of Origin            | India                              |
| Screw thread                 | -                                  |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 55.5 mm | 2.19 inch |
| Length                      | 18.8 mm | 0.74 inch |
| Height                      | 38 mm   | 1.5 inch  |
| Weight of std. Packing Unit | 2.93 Kg |           |

### Material Data

|                     |                                         |
|---------------------|-----------------------------------------|
| Insulating Material | Polyamide 6,6                           |
| Standard Colour     | Gray                                    |
| Colour Variants     | Red, Yellow, Blue, Black, Green, Khakhi |

### Rated Conductor Size

|                                      |                      |
|--------------------------------------|----------------------|
| Conductor cross section flexible min | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup>  |
| Conductor cross section solid min    | 0.08 mm <sup>2</sup> |
| Conductor cross section solid max    | 4 mm <sup>2</sup>    |

### Rated Conductor Size

|                                      |                      |
|--------------------------------------|----------------------|
| Conductor cross section flexible min | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup>  |

|                                   |                      |
|-----------------------------------|----------------------|
| Conductor cross section solid min | 0.08 mm <sup>2</sup> |
| Conductor cross section solid max | 4 mm <sup>2</sup>    |

## Product Accessories

### Marker For Terminal Blocks

|              |                 |                                                                                     |
|--------------|-----------------|-------------------------------------------------------------------------------------|
| LABEL KN5.08 | Pitch : 5.08 mm |  |
|--------------|-----------------|-------------------------------------------------------------------------------------|

### PLUG

|              |                                                                               |                                                                                     |
|--------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| PQPP2.5-F-8W | Height : 42.00 mm<br>Width : 15.80 mm<br>Pitch : 5.00 mm<br>Length : 40.00 mm |  |
|--------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|

