



PS8M-10W

Terminal Type - PS8M - 10W , Plug & socket type terminal block , nominal voltage: 800 V , nominal current: 32 A, connection method: Screw clamp connection , number of connections: 20 , Rated cross section: 6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS35/7.5 , TS35/15



Approvals



General Information

| | |
|------------------------------|---|
| Product Name | PS8M-10W |
| Connection Method | Screw Connection |
| Rating | 800 V / 32 A / 6 mm ² / 0.8 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty (in No) | 10 |
| Country Of Origin | India |
| Screw thread | M3.5 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 82 mm | 3.23 inch |
| Length | 94.6 mm | 3.72 inch |
| Height | 43.7 mm | 1.72 inch |
| Weight of std. Packing Unit | 1.55 Kg | |

Material Data

| | |
|---------------------|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red, Yellow, Blue, Black, Green, Khakhi |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 6 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 6 mm ² |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 6 mm ² |



| | |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 6 mm ² |

Product Accessories

DIN Rail Perforated

| | | |
|-------|--|---|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |

DIN Rail, Unperforated



| | | |
|------|--|--|
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |


End Cap



| | | |
|-----------|---|---|
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
|-----------|---|---|

End Clamp

| | | |
|--------|--|---|
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |

| End Clamp | | |
|-----------|---|---|
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |

| Marker For Terminal Blocks | | |
|----------------------------|-----------------|---|
| LABEL KN6.5 | Width : 6.70 mm |  |

| Marker carriers | | |
|-----------------|--|---|
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
| SCKNMLH | Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm |  |