


## SPT150

Terminal Type - SPT150, High current connectors with secured hinged cover, nominal voltage: 1000 V AC/1500 V DC, Rated cross-section - 150 mm<sup>2</sup>, nominal current: 320 A, connection method: Bolt connection, number of connections: 2, cross-section: 10 mm<sup>2</sup> - 150 mm<sup>2</sup>, 10 AWG - 350 KCMIL, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	SPT150
Connection Method	Bolt Connection
Rating	1000 V / 320 A / 150 mm <sup>2</sup> / 10 Nm
HSN Number	8904476702593
Standard Packing Qty (in No)	4
Country Of Origin	India
Screw thread	M10

### Dimensions & Weight

Width	42 mm	1.65 inch
Length	225.7 mm	8.89 inch
Height	80.3 mm	3.16 inch
Weight of std. Packing Unit	1.3 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	10 mm <sup>2</sup>
Conductor cross section flexible max	150 mm <sup>2</sup>
Conductor cross section solid min	10 mm <sup>2</sup>
Conductor cross section solid max	150 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	10 mm <sup>2</sup>
Conductor cross section flexible max	150 mm <sup>2</sup>

Conductor cross section solid min	10 mm <sup>2</sup>
Conductor cross section solid max	150 mm <sup>2</sup>


### Ratings - ATEX




ATEX Standard	EN 60079-7
ATEX Nominal Voltage U <sub>n</sub>	1000 V
ATEX Nominal Current I <sub>n</sub>	309 A
ATEX Cross Sec. Flexible Max.	150 mm <sup>2</sup>



### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U <sub>N</sub>	1000 V
B - UL Nominal Current I <sub>N</sub>	310 A
B - UL Wire Min	10 AWG
B - UL Wire Max	350 KCMIL

### Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

Fixed Bridge		
CCLASPT150-2W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
CCLASPT150-3W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	

Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	