


SPT150

Terminal Type – SPT150, High current connectors with secured hinged cover, nominal voltage: 1000 V AC/1500 V DC, Rated cross-section – 150 mm², nominal current: 320 A, connection method: Bolt connection, number of connections: 2, cross-section: 10 mm² – 150 mm², 10 AWG – 350 KCMIL, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SPT150
Connection Method	Bolt Connection
Rating	1000 V / 320 A / 150 mm ² / 10 Nm
HSN Number	8904476702593
Standard Packing Qty (in No)	4
Country Of Origin	India
Screw thread	M10

Dimensions & Weight

Width	42 mm	1.65 inch
Length	225.7 mm	8.89 inch
Height	80.3 mm	3.16 inch
Weight of std. Packing Unit	1.3 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	150 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	150 mm ²

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	150 mm ²

Conductor cross section solid min	10 mm ²
Conductor cross section solid max	150 mm ²

Ratings - ATEX


ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	1000 V
ATEX Nominal Current I _n	309 A
ATEX Cross Sec. Flexible Max.	150 mm ²

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	1000 V
B - UL Nominal Current I _N	310 A
B - UL Wire Min	10 AWG
B - UL Wire Max	350 KCMIL

Product Accessories


DIN Rail Perforated





CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
Fixed Bridge		
CCLASPT150-2W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
CCLASPT150-3W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	