


SPT95

Terminal Type – SPT95, High current connectors with secured hinged cover, nominal voltage: 1000 V AC/1500 V DC, Rated cross-section – 95 mm², nominal current: 232 A, connection method: Bolt connection, number of connections: 2, cross-section: 16 mm² - 95 mm², AWG: 14-3/0 mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SPT95
Connection Method	Bolt Connection
Rating	1000 V / 232 A / 95 mm ² / 6 Nm
HSN Number	85389000
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	M8

Dimensions & Weight

Width	32 mm	1.26 inch
Length	179.2 mm	7.06 inch
Height	70.6 mm	2.78 inch
Weight of std. Packing Unit	2.13 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	16 mm ²
Conductor cross section flexible max	95 mm ²
Conductor cross section solid min	16 mm ²
Conductor cross section solid max	95 mm ²

Rated Conductor Size

Conductor cross section flexible min	16 mm ²
Conductor cross section flexible max	95 mm ²

Conductor cross section solid min	16 mm ²
Conductor cross section solid max	95 mm ²

Ratings - CSA


CSA Standard	CSA C22.2NO 158
B - CSA Nominal Voltage U _N	1000 V
B - CSA Nominal Current I _N	200 A
B - CSA Wire Min	14 AWG
B - CSA Wire Max	3/0 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	1000 V
B - UL Nominal Current I _N	200 A
B - UL Wire Min	14 AWG
B - UL Wire Max	3/0 AWG

Product Accessories


DIN Rail Perforated





CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
Fixed Bridge		
CCLASPT70-2W	Width : 15.00 mm Thickness : 3.00 mm Pitch : 32.00 mm Length : 50.00 mm	
CCLASPT70-3W	Width : 15.00 mm Thickness : 3.00 mm Pitch : 32.00 mm Length : 82.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
GMH 20	Height : 51.00 mm Width : 20.00 mm Length : 41.50 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 41.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	