



## SQ4-2T

Terminal Type - SQ4-2T, Multi level Feed Through terminal block, connection method: Spring cage connection, Nominal Voltage : 1000 V , nominal Current : 32 A , number of connections: 4, cross section: 0.08 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG 24-10 , mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	SQ4-2T
Connection Method	Spring Cage Connection
Rating	1000 V / 32 A / 4 mm <sup>2</sup>
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	INDIA
Screw thread	-

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	88.1 mm	3.47 inch
Height	47 mm	1.85 inch
Weight of std. Packing Unit	1.7 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>

Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

### Ratings - ATEX

ATEX Standard	EN 60049-7
ATEX Nominal Voltage U <sub>n</sub>	630 V
ATEX Nominal Current I <sub>n</sub>	26 A
ATEX Cross Sec. Flexible Max.	4 mm <sup>2</sup>

### Ratings - CSA



CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U <sub>N</sub>	600 V
B - CSA Nominal Current I <sub>N</sub>	30 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	10 AWG


### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U <sub>N</sub>	600 V
B - UL Nominal Current I <sub>N</sub>	30 A
B - UL Wire Min	24 AWG
B - UL Wire Max	10 AWG

### Product Accessories

Cover Profile		
PCPDBF-5	Height : 14.10 mm Thickness : 1.50 mm Length : 113.00 mm	

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	

<b>DIN Rail, Unperforated</b>		
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

<b>End Cover</b>		
CSP4-2T	Height : 33.40 mm Width : 2.00 mm Length : 87.80 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	
<b>Partition Plate</b>		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
<b>Plug-in Bridge/Jumper</b>		
SLPU6-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 10.15 mm	
SLPU6-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 58.15 mm	
SLPU6-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 16.15 mm	
SLPU6-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 22.15 mm	
SLPU6-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 28.15 mm	
SLPU6-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 34.15 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

Marker carriers		
DSDDM2.5MLH	Height : 24.10 mm Width : 5.00 mm Length : 19.70 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

