


SQECD-2W

Terminal Type - SQECD , PCB Connector, Stack of 2 terminals with end cover, nominal voltage: 250 V, nominal current: 15 A, Pitch: 5.08 mm, connection method: Spring Cage connection, number of connections: 2 , cross-section: 0.5 mm² - 2.5 mm², AWG: 24 - 12, mounting type - Printed circuit board (PCB)



Approvals



General Information

| | |
|------------------------------|--|
| Product Name | SQECD-2W |
| Connection Method | Spring Cage Connection |
| Rating | 250 V / 15 A / 2.5 mm ² / NA Nm |
| HSN Number | 85389000 |
| Standard Packing Qty (in No) | 100 |
| Country Of Origin | India |
| Screw thread | NA |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 11.2 mm | 0.44 inch |
| Length | 15.4 mm | 0.61 inch |
| Height | 14.2 mm | 0.56 inch |
| Weight of std. Packing Unit | 0.35 Kg | |

Material Data

| | |
|---------------------|---------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | - |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |

Datasheet

| | |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Product Accessories

| End Cover | | |
|-----------|---|---|
| SQECDP | Height : 14.20 mm Width : 1.00 mm Length : 15.40 mm |  |

