
SQP2.5

Terminal Type –SQP2.5 , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , Rated cross section: 2.5 mm² , connection method: Spring Cage Connection, number of connections: 2, cross-section: 0.08 mm² – 4 mm², AWG : 24-12 , mounting type: Panel Mounted



Approvals

General Information

Product Name	SQP2.5
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm^2
HSN Number	8904476701503
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	5 mm	0.2 inch
Length	31.9 mm	1.26 inch
Height	21 mm	0.83 inch
Weight of std. Packing Unit	0.37 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.08 mm^2
Conductor cross section flexible max	2.5 mm^2
Conductor cross section solid min	0.08 mm^2
Conductor cross section solid max	4 mm^2

Rated Conductor Size

Conductor cross section flexible min	0.08 mm^2
Conductor cross section flexible max	2.5 mm^2

Conductor cross section solid min	0.08 mm^2
Conductor cross section solid max	4 mm^2

Ratings - ATEX


ATEX Standard	EN 60049-7
ATEX Nominal Voltage U_n	500 V
ATEX Nominal Current I_n	20 A
ATEX Cross Sec. Flexible Max.	2.5 mm^2

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	300 V
B - UL Nominal Current I_N	20 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG

Product Accessories

End Cover

CPP2.5	Height : 21.00 mm Width : 3.00 mm Length : 31.90 mm	

Marker For Terminal Blocks

LABEL KN5	Height : 2.42 mm Width : 5.00 mm Length : 7.50 mm	

Plug-in Bridge/Jumper

SLFP2.5-2W	Height : 20.60 mm Width : 6.40 mm Thickness : 2.00 mm Pitch : 4.95 mm	

Spacer Plate

SPP2.5	Height : 21.00 mm Width : 3.00 mm Length : 31.90 mm	