


SQTM2.5P4

Terminal Type -SQTM2.5P4, Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , connection method: Spring Cage Connection, number of connections: 4 (1 Input & 3 Output), Rated cross section: 2.5 mm² , cross-section: 0.08 mm² - 4 mm², mounting type: TS 15



Approvals



General Information

Product Name	SQTM2.5P4
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm ²
HSN Number	8904476705914
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	10 mm	0.39 inch
Length	33.3 mm	1.31 inch
Height	30 mm	1.18 inch
Weight of std. Packing Unit	0.47 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²

Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories

DIN Rail Perforated

CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
-----	---	---

End Cover

SQTMCP	Height : 22.20 mm Width : 4.00 mm Length : 32.00 mm	
--------	---	---

Marker For Terminal Blocks

KNLVR5	Height : 2.36 mm Width : 5.00 mm Thickness : 0.60 mm Pitch : 5.00 mm Length : 5.00 mm	
--------	---	---

Plug-in Bridge/Jumper

SLFP2.5-2W	Height : 20.60 mm Width : 6.40 mm Thickness : 2.00 mm Pitch : 4.95 mm	
------------	--	---