


SQTP2.5-12W

Terminal Type: SQTP2.5-12W , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , Rated cross section: 2.5 mm² , connection method: Spring Cage Connection, number of connections: 4, cross-section: 0.08 mm² – 4 mm², AWG : 24-12 , mounting type: Panel Mounted



Approvals



General Information

Product Name	SQTP2.5-12W
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm ²
HSN Number	8904476701398
Standard Packing Qty (in No)	5
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	5 mm	0.2 inch
Length	32 mm	1.26 inch
Height	22 mm	0.87 inch
Weight of std. Packing Unit	0.34 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²


Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²


Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories

Marker For Terminal Blocks

KNLVR5	Height : 2.36 mm	
	Width : 5.00 mm	
	Thickness : 0.60 mm	
	Pitch : 5.00 mm	
	Length : 5.00 mm	

Plug-in Bridge/Jumper

SLFP2.5-2W	Height : 20.60 mm	
	Width : 6.40 mm	
	Thickness : 2.00 mm	
	Pitch : 4.95 mm	

