SQTP2.5-7W

Terminal Type: SQTP2.5-7W , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , Rated cross section: 2.5 mm² , connection method: Spring Cage Connection, number of connections: 14, cross-section: 0.08 mm² – 4 mm², AWG : 24-12 , mounting type: Panel Mounted

Approvals

CE

General Information

Product Name	SQTP2.5-7W
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm^2
HSN Number	8904476701367
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	5 mm	0.2 inch
Length	32 mm	1.26 inch
Height	22 mm	0.87 inch
Weight of std. Packing Unit	0.4 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm^2
Conductor cross section flexible max	2.5 mm^2
Conductor cross section solid min	0.08 mm^2
Conductor cross section solid max	4 mm^2

Rated Conductor Size

Conductor cross section flexible min	0.08 mm^2
Conductor cross section flexible max	2.5 mm^2

Conductor cross section solid min	0.08 mm^2
Conductor cross section solid max	4 mm^2

Product Accessories

Marker For Terminal Blocks		
KNLVR5	Height : 2.36 mm Width : 5.00 mm Thickness : 0.60 mm Pitch : 5.00 mm Length : 5.00 mm	
Plug-in Bridge/Jumper		
SLFP2.5-2W	Height : 20.60 mm Width : 6.40 mm Thickness : 2.00 mm Pitch : 4.95 mm	