

## SQTP2.5-9W

Terminal Type: SQTP2.5-9W , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , Rated cross section: 2.5 mm<sup>2</sup> , connection method: Spring Cage Connection, number of connections: 4, cross-section: 0.08 mm<sup>2</sup> – 4 mm<sup>2</sup>, AWG : 24-12 , mounting type: Panel Mounted



### Approvals



### General Information

Product Name	SQTP2.5-9W
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm <sup>2</sup>
HSN Number	85389000
Standard Packing Qty (in No)	5
Country Of Origin	India
Screw thread	-

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	32 mm	1.26 inch
Height	22 mm	0.87 inch
Weight of std. Packing Unit	0.27 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>


### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>

Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

## Product Accessories

### Marker For Terminal Blocks

KNLVR5	Height	: 2.36 mm	
	Width	: 5.00 mm	
	Thickness	: 0.60 mm	
	Pitch	: 5.00 mm	
	Length	: 5.00 mm	

### Plug-in Bridge/Jumper

SLFP2.5-2W	Height	: 20.60 mm	
	Width	: 6.40 mm	
	Thickness	: 2.00 mm	
	Pitch	: 4.95 mm	

