

SQTP2.5P4-9W

Terminal Type -SQTP2.5P4-9W , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , connection method: Spring Cage Connection, number of connections: 36, Rated cross section: 2.5 mm² , cross-section: 0.08 mm² – 4 mm², AWG: 24-12 , mounting type: Panel Mounted



Approvals



General Information

Product Name	SQTP2.5P4-9W
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	5
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	105.8 mm	4.17 inch
Length	32 mm	1.26 inch
Height	22 mm	0.87 inch
Weight of std. Packing Unit	0.43 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²

Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories

Marker For Terminal Blocks

KNLVR5	Height : 2.36 mm	
	Width : 5.00 mm	
	Thickness : 0.60 mm	
	Pitch : 5.00 mm	
	Length : 5.00 mm	

Plug-in Bridge/Jumper

SLFP2.5-2W	Height : 20.60 mm	
	Width : 6.40 mm	
	Thickness : 2.00 mm	
	Pitch : 4.95 mm	

