



TQF4-2T+E

Terminal Type - TQF4-2T+E, Multi-tier terminal block with a fuse in the upper tier and with 1 connection for ground, nominal voltage: 500 V, nominal current: 6.3 A(UT), 32 A(LT), Rated cross-section – 4.0 mm², suitable size of cartridge fuse: 5X20 mm, connection method: Screw connection, number of connections: 5, cross-section: 0.14 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	TQF4-2T+E
Connection Method	Screw Connection
Rating	500 V / UT-6.3 A , LT-32 A / 4 mm ² / 0.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	92 mm	3.62 inch
Height	96 mm	3.78 inch
Weight of std. Packing Unit	1.2 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.14 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
--------------------------------------	----------------------

Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.14 mm ²
Conductor cross section solid max	6 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	300 V
B - CSA Nominal Current I _N	UL-6.3 A , LT-30 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	10 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	300 V
B - UL Nominal Current I _N	UL-6.3 A , LT-30 A
B - UL Wire Min	24 AWG
B - UL Wire Max	10 AWG

Product Accessories

Cover Profile

PCP120	Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm	
PCP500	Height : 9.50 mm Thickness : 1.50 mm Length : 126.00 mm	



DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
------	--	---

DIN Rail, Unperforated			
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm		
End Cap			
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm		
End Clamp			
SCUP	Height : 34.00 mm Length : 44.75 mm		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm		
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm		
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm		

Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Partition Plate		
BPN 120	Height : 102.50 mm Width : 3.00 mm Length : 125.00 mm	
Plug-in Bridge/Jumper		
SLPU6-2W	Height : 26.00 mm Width : 10.15 mm Pitch : 6.00 mm	
SLPU6-10W	Height : 26.00 mm Width : 58.15 mm Pitch : 6.00 mm	
SLPU6-3W	Height : 26.00 mm Width : 16.15 mm Pitch : 6.00 mm	
SLPU6-4W	Height : 26.00 mm Width : 22.15 mm Thickness : 2.50 mm Pitch : 6.25 mm	
SLPU6-5W	Height : 26.00 mm Width : 28.15 mm Pitch : 6.00 mm	
SLPU6-6W	Height : 26.00 mm Width : 34.15 mm Pitch : 6.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

Marker carriers		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	

