



## TQF6

Terminal Type - TQF6, Fuse terminal block, nominal voltage: 1000 V, nominal current: 10 A , Rated cross-section – 6 mm<sup>2</sup>, suitable size of cartridge fuse: 6.35X32 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	TQF6
Connection Method	Screw Connection
Rating	1000 V / 10 A / 6 mm <sup>2</sup> / 0.8 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3.5

### Dimensions & Weight

Width	8 mm	0.31 inch
Length	58.5 mm	2.3 inch
Height	70.7 mm	2.78 inch
Weight of std. Packing Unit	1.32 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	6 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	6 mm <sup>2</sup>

Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

### Ratings - CSA



CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U <sub>N</sub>	300 V
B - CSA Nominal Current I <sub>N</sub>	6.3 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	8 AWG


### Ratings - UL


UL Standard	UL 1059
B - UL Nominal Voltage U <sub>N</sub>	300 V
B - UL Nominal Current I <sub>N</sub>	6.3 A
B - UL Wire Min	24 AWG
B - UL Wire Max	8 AWG







### Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

<b>Marker For Terminal Blocks</b>		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	

<b>Partition Plate</b>		
DBF-6	Height : 81.50 mm Width : 3.00 mm Length : 85.00 mm	

<b>Plug-in Bridge/Jumper</b>		
MLPU8-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 79.20 mm	
MLPU8-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 15.20 mm	
MLPU8-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm	
MLPU8-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 31.20 mm	
MLPU8-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 39.20 mm	
MLPU8-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 47.20 mm	

<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	