


KNL4

Neutral link Type - KNL4 , Neutral link for shield on busbars, Nominal voltage: 800 V , Nominal current: 41 A, Connection method: Screw connection, number of connections: 1, Rated cross section: 6.0 mm² , cross section: 0.5 mm² - 6 mm², mounting type: Neutral Busbar



Approvals

CE

General Information

Product Name	KNL4
Connection Method	Screw Connection
Rating	800 V / 41 A / 6 mm ² / 0.8 Nm
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	24 mm	0.94 inch
Height	30 mm	1.18 inch
Weight of std. Packing Unit	0.66 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green
Colour Variants	Black, Green

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²


Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Product Accessories

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Clamp

SCNL	Height : 44.10 mm Width : 9.50 mm Length : 50.00 mm	
------	---	---

Marker For Terminal Blocks

LABEL KN6.5	Width : 6.70 mm	
-------------	-----------------	---

Support Bracket

KNLSUP	Height : 18.35 mm Width : 19.00 mm Length : 23.00 mm	
--------	--	---

Neutral busbar

KNLB10	Width : 10.00 mm Thickness : 3.00 mm Length : 1,000.00 mm	
--------	---	---

Neutral busbar				
KNLB6	Width	: 6.00 mm		
	Thickness	: 6.00 mm		
	Length	: 1,000.00 mm		

