


CLTDM4

Terminal Type - CLTDM4 , Test Disconnect Terminal Block , nominal voltage: 1100 V, nominal current: 45 A, connection method: Bolt connection, number of connections: 2, Rated cross section: 6 mm², cross section: 2.5 mm² - 6 mm² , mounting type: TS32



Approvals



General Information

Product Name	CLTDM4
Connection Method	Bolt Connection
Rating	1100 V/45 A/6 mm ² /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	M4

Dimensions & Weight

Width	13 mm	0.51 inch
Length	69 mm	2.72 inch
Height	50 mm	1.97 inch
Weight of std. Packing Unit	2.21 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	2.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	2.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1100 V
Nominal Current I_n	45 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

