


CST25

Terminal Type - CST25, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 101 A, Rated cross-section - 25 mm², connection method: Screw connection, number of connections: 2, cross-section: 6 mm² - 35 mm², mounting type: TS32



Approvals



General Information

Product Name	CST25
Connection Method	Screw Connection
Rating	800 V/101 A/25 mm ² /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	12.5 mm	0.49 inch
Length	45 mm	1.77 inch
Height	59.5 mm	2.34 inch
Weight of std. Packing Unit	3.09 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	25 mm ²
Conductor cross section solid min	6 mm ²
Conductor cross section solid max	35 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-1-1
Nominal Voltage U_n	800 V
Nominal Current I_n	101 A
Nominal cross section	25 mm ²
Short-time current	3 kA
Rated surge voltage	8 kV
Degree of pollution	3

