


DBK1X6

Terminal Type - DBK1X6 , Distribution Block, nominal voltage: 800 V, nominal current: IC-114 A , OG-57 A , connection method: 1 Nut connection for IC & Screw connection for OG, number of connections: 13, cross section: IC-10 -50 mm² , OG-2.5 - 16 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	DBK1X6
Connection Method	1 nut connection for IC & Screw clamp connection for OG
Rating	800 V/IC-114 A, OG-57 A/IC-35 mm ² , OG-10 mm ² /IC-6 Nm , OG-1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	IC-M8 , OG-M4

Dimensions & Weight

Width	68 mm	2.68 inch
Length	94.05 mm	3.7 inch
Height	49.7 mm	1.96 inch
Weight of std. Packing Unit	1.76 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	IC-10 mm ² , OG-2.5 mm ²
Conductor cross section flexible max	IC-50 mm ² , OG-10 mm ²
Conductor cross section solid min	IC-10 mm ² , OG-2.5 mm ²
Conductor cross section solid max	IC-50 mm ² , OG-16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	IC-114 A, OG-57 A
Nominal cross section	IC-35 mm ² , OG-10 mm ²
Short-time current	4.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

