



DCF4D1

Terminal Type - DCF4D1 , Fuse terminal block with LED of 24 VDC for fuse failure indication , nominal voltage: 800 V, nominal current: 10 A ,Rated cross-section – 4 mm², suitable size of cartridge fuse : 5X20 mm and 5x25 mm, connection method: Spring Cage connection, number of connections: 2, cross section: 0.5 mm² - 4 mm² , mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DCF4D1
Connection Method	Spring Cage Connection
Rating	800 V/10 A/4 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	8 mm	0.31 inch
Length	60 mm	2.36 inch
Height	66.6 mm	2.62 inch
Weight of std. Packing Unit	1.45 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-3
Nominal Voltage U_n	800 V
Nominal Current I_n	10 A
Nominal cross section	4 mm ²
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

