


## DPBB185N

Terminal Type - DPBB185N, High Current connectors, nominal voltage: 1000 V, nominal current: 353 A, Rated cross-section - 185 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross-section: 50 mm<sup>2</sup> - 185 mm<sup>2</sup>, mounting type: TS 35/15, TS 32



### Approvals



### General Information

Product Name	DPBB185N
Connection Method	Bolt Connection
Rating	1000 V/353 A/185 mm <sup>2</sup> /14 Nm
HSN Number	85389000
Standard Packing Qty(in No)	4
Country Of Origin	India
Screw thread	M12

### Dimensions & Weight

Width	53 mm	2.09 inch
Length	115 mm	4.53 inch
Height	53.3 mm	2.1 inch
Weight of std. Packing Unit	1.49 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	50 mm <sup>2</sup>
Conductor cross section flexible max	185 mm <sup>2</sup>
Conductor cross section solid min	50 mm <sup>2</sup>
Conductor cross section solid max	185 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	353 A
Nominal cross section	185 mm <sup>2</sup>
Short-time current	22.2 kA
Rated surge voltage	12 kV
Degree of pollution	3

